

NATURAL HEATING

PRODUCT INFORMATION



- Cast iron flue that is 360°-regulated allows to evacuate waste in any direction.
- Grateless hearth allows the so-called afterburning on ash.
- Decor glass included provides an attractive exposure of fire.
- Selectable height control allows to adjust fireplace insert height to the installation spot.
- Combustion chamber coated with a special concrete that accumulates warmth, fire-resistant up to 1000°C.
- Depth of device insert adapted to shallow casing.
- Integrated 4-degree throttle regulates primary and secondary air transfer.

GUILLOTINE HORIZONTAL FIREPLACE INSERT HST54X39.G

Nominal power	11,2 kW
Thermal efficiency	75 %
CO emission (with 13% O ₂)	0,507 g/m ³
Dust emission (with 13% O ₂)	0,037 g/m ³
Exhaust temperature	296°C
Maximum log length	300 mm
Material	boiler steel 4mm P265GH
Draft hood diameter	160 mm
Air intake diameter	125 mm
Recommended active field of exhaust grilles	420-480 cm ²
Recommended active field of intake grilles	240-390 cm ²
Size of fireplace glass	540x390 mm
Weight	180 kg
Fuel type	12-20% humidity seasoned hardwood (beech, birch, hornbeam)

